

DICENTIS Wireless Devices

www.boschsecurity.com



BOSCH
Invented for life



- ▶ 4.3 inch capacitive touch screen and built-in NFC reader for user identification
- ▶ Personalizable by adding a custom logo in screen
- ▶ Removable Battery Pack, easy to change and charge
- ▶ Can be configured as participant, dual-use or chairperson Wireless Device by web interface
- ▶ Future proof expendability with software modules without hardware modification

To the participant the most important part of a DICENTIS Wireless Conference System is the discussion device. The Wireless Devices (DCNM-WD and DCNM-WDE) have an elegant design and are used to participate in a meeting.

The Wireless Device enables participants to speak, register a request-to-speak, and listen to the speaker. The DCNM-WD is used as a basic single-use, dual-use or chairperson Wireless Device, while the DCNM-WDE Wireless Device Extended is extended with Near Field Communication (NFC) reader user identification and 4.3 inch capacitive touch screen.

The web interface of the Wireless Access Point (DCNM-WAP) is used to configure the Wireless Device as a single-use, dual-use, or chairperson Wireless Device.

Functions

General

- The Wireless Devices connects to the DCNM-WAP.
- Single-use, dual-use or chairperson can be configured via the web interface.
- Audio mute button.
- Operating in the 2.4 GHz and 5 GHz (UNII1, 2 (extended) and 3) (license free) band.

DCNM-WD

- Used for basic discussion.

DCNM-WDE

- Used for extended discussion, including:
 - 4.3" capacitive touch screen:
 - Add custom logo in screen.
 - Speaker list.
 - Request list.
 - Identification functionality.
 - Future upgradable functionality.
 - Camera control.
 - Voting.
 - Logon identification.
 - Multiple languages.
- Built-in Near Field Communication (NFC) contactless tag reader.

Speech intelligibility

- Maximum speech intelligibility is guaranteed at all times.
- The Wireless Device connects to the DCNM-WAP.
- The Wireless Devices produce crystal-clear sound due to a very high signal-to-noise ratio and smart frequency selection.
- The loudspeaker and microphone can be active at the same time for a face-to-face meeting experience. To prevent acoustic feedback, a feedback suppressor is built-in.

Zero Interference

- Based on standard WiFi.
- Seamless automatic frequency channel switching.

- WiFi coverage area range test.
- Packet Loss Concealment.

Security

- The DICENTIS Wireless Conference System and Wireless Devices have secure connectivity using WPA2 to prevent eavesdropping and unauthorized access.
- Encryption ensures the information within the system remains confidential.

Microphones

- A socket is provided to connect the pluggable microphone (DCNM-HDMIC, DCNM-MICS or DCNM-MICL, all to be ordered separately).

Headphones and loudspeakers

- The Wireless Devices accommodate two headphone connections and controls (on the left and right hand side), so the speaker can be heard clearly even with excessive background noise.

Battery maintenance

- Rechargeable Battery Pack (DCNM-WLIION).
- The lithium-ion Battery Pack can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.
- Smart battery management via web interface control (battery status and usage counting time).

Controls and Indicators

- On top side:
 - 4.3 inch capacitive display with touch screen (DCNM-WDE only).
 - Microphone with a red or green indicator:
 - **Red** indicates microphone is active.
 - **Green** indicates request-to-speak accepted.
 - LED indicators on device showing:
 - Microphone on state – **Red**.
 - Possible-to-speak – **White**.
 - Priority – **White** (Chairperson only).
 - Request-to-speak – **Green**.
- On the left and right hand side
 - Headphone rotary volume controls.
- On rear side:
 - Yellow out-of-range of Wireless Access Point LED indicator.
 - Red battery low LED indicator.
- Under base side:
 - Recessed, so called ‘De-init,’ switch to disconnect the connected Wireless Device with the Wireless Access Point (DCNM-WAP).

Interconnections

- Socket for pluggable microphone.
- Two 3.5 mm (0.14 in) headphone sockets stereo jack type.

Certifications and approvals

EU	CE
US	FCC
CA	ICES-003
KR	KC

AU/NZ	RCM
RU/KZ/BY	EAC
JP	MIC
CN	China RoHS, CMIIT
SA	SASO
BR	ANATEL

Parts included

Quantity	Components
1	DCNM-WD or DCNM-WDE Wireless Device

Technical specifications

Electrical

Supply voltage (battery pack)	7.5 Vdc
Power consumption	4 W
Operating time DCNM-WD	> 24 hours (20% speech, 80% listening)
Operating time DCNM-WDE	> 20 hours (20% speech, 80% listening)
Frequency response	100 Hz – 20 kHz (-3 dB at nominal level)
THD at nominal level	< 0.1 %
Dynamic range	> 90 dB
Signal-to-noise ratio	> 90 dB
Headphone load impedance	> 32 ohm < 1k ohm
Headphone output power	15 mW

Radio

WiFi standard	IEEE 802.11n
Frequency Range	2.4 GHz and 5 GHz (ISM license free)

Audio inputs

Nominal microphone input	80 dB SPL according IEC60914
Maximum microphone input	110 dB SPL according IEC60914

Audio outputs

Loudspeaker nominal output	72 dB SPL at 0.5 m
Loudspeaker maximum output	80 dB SPL
Headphone nominal output	0 dBV
Headphone maximum output	3 dBV

General

Screen size (DCNM-WDE only)	4.3 inch
Screen type (DCNM-WDE only)	Capacitive multi touch
Supported contactless NFC tag (DCNM-WDE only)	According to: ISO/IEC14443 Type A (from 106 kbps to 848 kbps. MIFARE 106kbps).

Mechanical

Mounting	Tabletop
Dimensions (H x W x D) without microphone	259 x 139 x 72 mm (10.2 X 5.5 x 2.8 in)
Weight:	
DCNM-WD	590 g (1.30 Lb)
DCNM-WD + Battery Pack	1051 g (2.32 lb)
DCNM-WDE	670 g (1.47 lb)
DCNM-WDE + Battery Pack	1131 g (2.49 lb)
Color (top and base)	Traffic black (RAL 9017)

Environmental

Operating temperature	5 °C to +45 °C (41 °F to +113 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Relative humidity	< 95 %, > 5%

Ordering information**DICENTIS Wireless Device**

DECENTIS Wireless Device. Pluggable microphone and battery pack to be ordered separately.

Order number **DCNM-WD**

DICENTIS Wireless Device Extended

DECENTIS Wireless Device Extended with 4.3 inch touch screen, NFC identification reader. Pluggable microphone and battery pack to be ordered separately.

Order number **DCNM-WDE**

Accessories**DICENTIS Battery Pack**

Battery Pack for Wireless Device (DCNM-WD and DCNM-WDE), lithium-ion, 7.5 Vdc, 12800 mAh, color: Charcoal.

Order number **DCNM-WLIION**

DICENTIS Transport Case for 8 Devices

Transport Case for storing and transporting one Wireless Access Point (DCNM-WAP), 8 Wireless Devices (DCNM-WD and/or DCNM-WDE), 8 high directive microphones (DCNM-HDMIC), 8 short or long Stem Microphones (DCNM-MICS/L).

Order number **DCNM-TC**

DCN multimedia High Directive Microphone

DCN multimedia High Directive Microphone for the DICENTIS Wireless Devices and DCN multimedia devices.

Order number **DCNM-HDMIC**

DCN multimedia Short Stem Microphone

DCN multimedia Short Stem Microphone for the DICENTIS Wireless Devices and DCN multimedia device.

Order number **DCNM-MICS**

DCN multimedia Long Stem Microphone

DCN multimedia Long Stem Microphone for the DICENTIS Wireless Devices and DCN multimedia device.

Order number **DCNM-MICL**

ACD-MFC-ISO 50/each

MIFARE Classic ID card with 1 kByte data storage, 2 application areas, one of which can be customized.

Packing information: 50 cards/ each unit

Order number **ACD-MCF-ISO**

ACD-EV1-ISO 50/each

Mifare DESFire EV1 ID card with 8 kByte data storage, 2 application areas, one of which can be customized.

Packing information: 50 cards/ each unit

Order number **ACD-EV1-ISO**

Software Options**DCN multimedia Voting at Seat**

The DCN multimedia Voting at Seat license extends DICENTIS Wireless Devices Extended and DCN multimedia devices with voting functionality.

Order number **DCNM-LSVT**

DCN multimedia Identification at Seat

The DCN multimedia Identification at Seat license extends DICENTIS Wireless Devices Extended and DCN multimedia devices with identification functionality.

Order number **DCNM-LSID**

DCN multimedia Dual Use at Seat

This license extends the DICENTIS Wireless Device with dual-use functionality. If the DCNM-LSID and/or DCNM-LSVT licenses are activated, two copies of these licenses are also required for each dual-use Wireless Device.

Order number **DCNM-LSDU**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com